

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150512-E40857  
**Report Reference** E40857-19821229  
**Issue Date** 2015-MAY-12

**Issued to:** UNITED ELECTRIC CONTROLS CO  
180 DEXTER AVE  
PO BOX 9143  
WATERTOWN MA 02472

**This is to certify that representative samples of** FLOAT- AND PRESSURE-OPERATED MOTOR CONTROLLERS FOR USE IN HAZARDOUS LOCATIONS  
See Addendum page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 1203 - Explosion-Proof and Dust-Ignition-Proof Electrical Equipment for Use in Hazardous (Classified) Locations  
CAN/CSA C22.2 No. 25-1966 - Enclosures for Use in Class II, Groups E, F, and G Hazardous Locations  
CAN/CSA C22.2 No. 30-M1986 - Explosion-Proof Enclosures for Use in Class I Hazardous Locations

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150512-E40857  
**Report Reference** E40857-19821229  
**Issue Date** 2015-MAY-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL 120 Series Pressure or Differential Pressure-Operated Switch for use in Class I, Groups B, C and D; Class II, Groups E, F and G; Class III. Cat. Nos. H or J, with or without prefix Q; followed by 120, 121 or 122; may be followed by K or P; followed by two to five character/digit alphanumeric code; followed by four digit numeric code; may be followed by four to five character/digit alphanumeric code or may be followed by five character/digit alphanumeric customer specification code. Enclosure Type 4X.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

