

FOR ASSEMBLY REF: M-12452

MANUFACTURING INSTRUCTIONS:

1. ASSEMBLE TERMINAL BLOCK ASSY., ITEM #12, TO SWITCH, ITEM #11, USING SCREWS SUPPLIED WITH SWITCH


CUSTOMER
UEC STANDARD

UE TYPE
J120-15622

SPECIFICATIONS:
SAME AS J120-704 EXCEPT:
ADJUSTABLE DIFFERENTIAL SWITCH
WETTED MATERIAL: st/st PRESSURE CONNECTION
VITON DIAPHRAGM AND O'RING
RANGE: 20 TO 200 psi
DEADBAND: 12 TO 26 psi; BETWEEN 80 & 140 psi

NOTE: AGENCY CRITICAL DRAWING, REVISIONS MUST BE REVIEWED FOR CERTIFICATION IMPACT.

SYM	DESCRIPTION	DATE	DWN	APPD
B	CHANGED CUST TO UEC ECN#E0297	4/16/03	AB	LK
A	FIRST ISSUE. ECN#E0252	3/10/03	PLW	L.K.
REVISIONS				

ORIGINAL DATE	3/10/03	TITLE	J120-15622	DF001
DRWN	PLW			REV. B
CHKD	A.B.			
APPD	LEVON			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FRACTIONS ±1/64 2 PLACE DEC 3 PLACE DEC ANGLES ±.010 ±.005 ±1/2°				
DO NOT SCALE THIS DRAWING			SCALE	NONE
				 UNITED ELECTRIC CONTROLS COMPANY WATERTOWN * MASSACHUSETTS
				DWG NO 12452-2