


MAXIMUM PRESSURE: 600 psi / 41.4 bar
 AMBIENT TEMPERATURE RANGE: 0 TO 160°F
 TERMINAL SCREWS: #6-32
 SWITCH ACTION: SPDT
 ELECTRICAL RATING: 20A / 480 VAC
 WETTED MATERIAL:
 SENSOR BUNA-N OR DACRON (SENSOR 2),
 VITON (SENSOR 3),
 EPDM (SENSOR 4)
 PRESSURE CONNECTION: BRASS
 UL LISTED, cUL CERTIFIED, CE APPROVED (PENDING)

C	25 to 475	1.7 to 32.8	10 to 25	0.7 to 1.7
B	20 to 200	1.4 to 13.8	4 to 10	0.3 to 0.7
A	3 to 30	0.2 to 2.1	2 to 5	0.1 to 0.3
MODEL NO.	psi	bar	psi	bar
	ADJUSTABLE RANGE		DEADBAND	

SYM	DESCRIPTION	DATE	DWN	APPD
B	CHANGED KPa TO bar. ECN# E0054	10/9/02	PLW	H.N.
A	FIRST ISSUE. ECN#C8029	4-23-99	S.R.	A.M.

ORIGINAL DATE 4-23-99
 DRWN S. ROBAK
 CHKD A.B.
 APPD A. MINASSIAN
 UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES

TITLE
 25 SERIES
 MODELS
 A, B & C

DF001
 REV. B

 UNITED ELECTRIC
 CONTROLS COMPANY
 WATERTOWN * MASSACHUSETTS

DWG NO
 A-13490

DO NOT SCALE THIS DRAWING

SCALE 0.75:1