

$\frac{1}{8}$ NPT (PRESS CONNECTION E)
 $\frac{1}{4}$ NPT (PRESS CONNECTION F)

MAXIMUM PRESSURE: 600 psi / 41.4 bar
 AMBIENT TEMPERATURE RANGE: 0 TO 160°F
 TERMINAL SCREWS: #6-32
 SWITCH ACTION: SPDT
 ELECTRICAL RATING: 20A / 480 VAC
 WETTED MATERIAL:
 SENSOR BUNA-N OR DACRON (SENSOR 2),
 VITON (SENSOR 3),
 EPDM (SENSOR 4)
 PRESSURE CONNECTION: BRASS
 UL LISTED, cUL CERTIFIED, CE APPROVED (PENDING)

C	25 to 475	1.7 to 32.8	35 to 140	2.4 to 9.7
B	20 to 200	1.4 to 13.8	16 to 70	1.1 to 4.8
A	3 to 30	0.2 to 2.1	4 to 11	0.3 to 0.8
MODEL NO.	psi	bar	psi	bar
	ADJUSTABLE RANGE		DEADBAND	

SYM	DESCRIPTION	DATE	DWN	APPD
C	CHANGED KPa to bar. ECN# E0054	10/9/02	PLW	H.N.
B	ADDED PEM FASTENER. ECN#C8232	7-9-99	S.R.	A.M.
A	FIRST ISSUE. ECN#C8029	4-23-99	S.R.	A.M.


REVISIONS

ORIGINAL DATE	4-23-99
DRWN	S. ROBAK
CHKD	A.B.
APPD	A. MINASSIAN
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
DO NOT SCALE THIS DRAWING	

TITLE
**25 SERIES
 MODELS
 A, B & C
 ADJ. DEADBAND**

SCALE 0.75:1

DF001
REV. B



UNITED ELECTRIC
 CONTROLS COMPANY
 WATERTOWN * MASSACHUSETTS

DWG NO
A-13491