

CUSTOMER:
U.E.C.

CUSTOMER PART NO.:
(FOR HEAT TRACE APPLICATIONS)

U.E. TYPE:
B100-13546


SPECIFICATIONS:
RANGE: 15 TO 140°F
ELECTRICAL RATING: 22 A 480 VAC
#304 st/st STEM (NO THREADS)
cULus LISTED.
TYPE 4X ENCLOSURE

SYM	DESCRIPTION	DATE	DWN	APPD
C	SET POINT REMOVED ECN#E7482	4/29/24	KLF	RCI
B	CHANGED: *UL LISTED, cUL CERTIFIED* TO *cULus LISTED*. CHANGED: *CONFORMS TO NEMA 4X REQUIREMENTS* TO *TYPE 4X ENCLOSURE*. DELETED: I & M SHEET IMT100. ECN#E4978	11-25-13	SR	EM
A	FIRST ISSUE. REPLACES SPEC. SHEET: 12711-1. ECN#E3275	8-11-09	SR	RAM
REVISIONS				

ORIGINAL DATE	8-11-09
DRWN	S. ROBAK
CHKD	PLW
APPD	R. MCCAREY
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
TOLERANCES ON FRACTIONS ±1/64	
2 PLACE DEC 3 PLACE DEC ANGLES ±0.010 ±0.005 ±1/2°	
DO NOT SCALE THIS DRAWING	

TITLE	B100-13546
UE STD HEATRACE	
SCALE	NONE

DF001D



UNITED ELECTRIC
CONTROLS COMPANY
WATERTOWN * MASSACHUSETTS

DWG NO
A-13954