

**SPECIFICATIONS:**  
UE TYPE: J54S-16008


RANGE: 30 TO 300 psi  
 MAX. WORKING PRESSURE: 100 psi ABOVE SET POINT  
 PROOF PRESSURE: 200 psi ABOVE SET POINT, MAX 600 psi.  
 ADJUSTABLE DEAD-BAND: 10 TO 30 psi  
 ELECTRICAL RATING: 20A 480 VAC  
 WETTED MATERIALS: ALUMINUM, BUNA-N, BRASS  
 PRESSURE CONNECTION: 1/4" NPT(M).  
 ADJUSTMENT TYPE: ADJUSTMENT SCREW.  
**APPROVALS:**  
 UL LISTED, CSA CERTIFIED.  
 CE COMPLIANT TO LOW VOLTAGE DIRECTIVE.

A	FIRST ISSUE, ECN# E3303	9-15-09	DWD	LK
SYM	DESCRIPTION	DATE	DWN	APPD
REVISIONS				

ORIGINAL DATE	9-15-09
DRWN	DWD
CHKD	PLW
APPD	LK
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON FRACTIONS ±1/64 2 PLACE DEC 3 PLACE DEC ANGLES ±.010 ±.005 ±1/2°	
DO NOT SCALE THIS DRAWING	

TITLE	J54S-16008
SCALE	3/4

DF002  
REV. A



UNITED ELECTRIC  
CONTROLS COMPANY  
WATERTOWN \* MASSACHUSETTS

DWG NO  
A-13955