


CUSTOMER:
U.E.C.

CUSTOMER PART NO.:
(FOR HEAT TRACE APPLICATIONS)

U.E. TYPE:
B100-13546

SPECIFICATIONS:
RANGE: 15 TO 140°F
ELECTRICAL RATING: 22 A 480 VAC
#304 st/st STEM (NO THREADS)
cULus LISTED.
TYPE 4X ENCLOSURE

C	SET POINT REMOVED ECN#E7482	4/29/24	KLF	RCI	ORIGINAL DATE 8-11-09	TITLE B100-13546	 UNITED ELECTRIC CONTROLS COMPANY WATERTOWN * MASSACHUSETTS
B	CHANGED: *UL LISTED, cUL CERTIFIED* TO *cULus LISTED*. CHANGED: *CONFORMS TO NEMA 4X REQUIREMENTS* TO *TYPE 4X ENCLOSURE*. DELETED: I & M SHEET IMT100. ECN#E4978	11-25-13	SR	EM	DRWN S. ROBAK		
A	FIRST ISSUE. REPLACES SPEC. SHEET: 12711-1. ECN#E3275	8-11-09	SR	RAM	CHKD PLW		
SYM	DESCRIPTION	DATE	DWN	APPD	APPD R. MCCAREY		
REVISIONS					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	UE STD HEATRACE	DWG NO A-13954
					TOLERANCES ON FRACTIONS ±1/64 2 PLACE DEC 3 PLACE DEC ANGLES ±0.010 ±0.005 ±1/2° DO NOT SCALE THIS DRAWING		