


NEMA 4 & 4X REPLACEMENT HEADS AND TERMINAL BLOCKS

CAST ALUMINUM – gasketed screw cover

NEMA 4 with gasketed screw cover and stainless steel chain;
4-post ceramic terminal block included. For epoxy-coated, NEMA
4X, add suffix-E to part#. (e.g., PH01E)

Ordering Code	Process Conn.	Conduit Conn.
PH01	1/2"	1/2"
PH02	1/2"	3/4"
PH03	3/4"	3/4"




PH01 - PH06

CAST IRON – NEMA 4, gasketed screw cover

NEMA 4 with gasketed screw cover and stainless steel chain;
4-post ceramic terminal block included. For epoxy-coated, NEMA
4X, add suffix-E to part #. (e.g., PH04E)

Ordering Code	Process Conn.	Conduit Conn.
PH04	1/2"	1/2"
PH05	1/2"	3/4"
PH06	3/4"	3/4"




PH45

CAST ALUMINUM – flip-top cover

NEMA 4 with flip-top cover and latching closure, 4-post ceramic
terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH45	1/2"	3/4"



PH47

316 STAINLESS STEEL – NEMA 4X, gasketed screw cover


NEMA 4X with gasketed screw cover and stainless steel chain;
4-post ceramic terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH47	1/2"	3/4"

BLACK POLYPROPYLENE – NEMA 4, gasketed screw cover

NEMA 4 with gasketed screw cover, 4-post ceramic terminal block
included.

Ordering Code	Process Conn.	Conduit Conn.
PH23	1/2"	3/4"




PH23 - PH24

WHITE POLYPROPYLENE – NEMA 4, gasketed screw cover

NEMA 4 with gasketed screw cover and stainless steel chain;
4-post ceramic terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH24	1/2"	3/4"



PH26

NYLON – NEMA 4, gasketed screw cover


Gasketed screw cover, 4-post ceramic terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH26	1/2"	1/2"

CERAMIC TERMINAL BLOCK REPLACEMENTS

For NEMA 4 heads, brass terminals

Ordering Code	No. of Terminals	Max. Wire Size
PH39	2	8 AWG.
PH40	3	8 AWG.
PH41	4	8 AWG.
PH42	6	14 AWG.




PH41

EXPLOSION-PROOF REPLACEMENT HEADS AND TERMINAL BLOCKS

CAST ALUMINUM – FM/CSA approved

FM/CSA approved for Class I, Div. 1, Groups B, C, D; Class II, Groups E, F, G; gasketed screw cover and stainless steel chain; 6-post ceramic terminal block included. For epoxy-coated, add suffix-E to part #. (e.g., PH50E)

Ordering Code	Process Conn.	Conduit Conn.
PH50	1/2"	1/2"
PH51	1/2"	3/4"
PH52	3/4"	3/4"




PH50-52,
PH56-57

STAINLESS STEEL – FM/CSA approved

FM/CSA approved for Class I, Div. 1, Groups B, C, D; Class II, Groups E, F, G; gasketed screw cover and stainless steel chain; 6-post ceramic terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH56	1/2"	1/2"
PH57	1/2"	3/4"




PH53

CAST ALUMINUM – ATEX approved

ATEX approved for EEx d IIC, gasketed screw cover and stainless steel chain; 3-post ceramic terminal block included.

Ordering Code	Process Conn.	Conduit Conn.
PH53	1/2"	3/4"



PH17-19

CAST ALUMINUM – UL/CSA approved


UL/CSA approved for Class I, Div. 1, Groups C, D; Class II, Groups E, F, G; screw cover; 4-post plastic terminal strip included. For epoxy-coated, add suffix-E to part #. (e.g., PH17E)

Ordering Code	Process Conn.	Conduit Conn.
PH17	1/2"	1/2"
PH18	1/2"	3/4"
PH19	3/4"	3/4"

PLASTIC TERMINAL STRIP REPLACEMENTS

For explosion-proof heads (PH17-PH22), brass terminals

Ordering Code	No. of Terminals	Length of Strip
PH43-4	4	2.16"
PH43-6	6	2.91"




PH43

CERAMIC TERMINAL BLOCK REPLACEMENTS

For explosion-proof heads (PH50-PH52), brass terminals

Ordering Code	No. of Terminals	Max. Wire Size
PH48	3	8 AWG.
PH49	6	14 AWG.




PH49

PARTS TO CONNECT TO WIRING OR THE PROCESS

COMPRESSION FITTINGS			
For 1/8" diameter sheath			
Part Number	NPT	Body/Nut	Ferrule
PF38	1/8"	304 stst	304 stst
PF39	1/8"	304 stst	Teflon®
PF40	1/4"	304 stst	304 stst
PF41	1/4"	304 stst	Teflon®
For 3/16" diameter sheath			
PF52	1/8"	304 stst	304 stst
PF53	1/8"	304 stst	Teflon®
PF54	1/8"	Brass	Brass
PF55	1/4"	304 stst	304 stst
PF56	1/4"	304 stst	Teflon®
PF59	1/2"	304 stst	304 stst
PF60	1/2"	304 stst	Teflon®
For 1/4" diameter sheath			
PF63	1/8"	304 stst	304 stst
PF65	1/4"	304 stst	304 stst
PF66	1/4"	304 stst	Teflon®
PF67	1/4"	Teflon®	Teflon®
PF68	1/4"	Brass	Brass
PF73	1/2"	304 stst	304 stst
PF74	1/2"	304 stst	Teflon®
PF75	1/2"	Brass	Brass
PF76	1/2"	Teflon®	Teflon®




PF38 to PF75







PF13 to PF18

SPRING-LOADED FITTINGS			
Standard, Non-sealed			
Part Number	Process Conn.	Conduit Conn.	Sensor Diameter
PF13	1/2" NPT	1/2" NPT	3/16"
PF14	1/2" NPT	1/2" NPT	1/4"
PF17	3/4" NPT	3/4" NPT	3/16"
PF18	3/4" NPT	3/4" NPT	1/4"
O-Ring Sealed*			
PF21	1/2" NPT	1/2" NPT	3/16"
PF22	1/2" NPT	1/2" NPT	1/4"
PF25	3/4" NPT	3/4" NPT	3/16"
PF26	3/4" NPT	3/4" NPT	1/4"
Notes:			
1. Maximum pressure rating 15 psi			
2. Buna N O-ring rated for -23 to 93°C (-10 to 200°F)			



PF21 to PF26

PLUGS AND JACKS	
(Note: specify J, K, E or T calibration. e.g., PT05-J)	
PT05	Standard plug, rated to 177°C (350°F)
PT06	Standard jack, rated to 177°C (350°F)
PT07	High Temp. plug, rated to 260° (500°F)
PT08	High Temp. jack, rated to 260° (500°F)
PT09	Miniature plug, rated to 177°C (350°F)
PT10	Miniature jack, rated to 177°C (350°F)
PA9	Rubber boot for use with PT05/PT06
PA10	Cable clamp for PT05 to PT08
PA11	Neoprene bushing for use with PA10 to prevent wire abrasion



BAYONET ADAPTERS (PLATED STEEL)		
Part Number	Thread Size	Length (L)
PA20	1/8" - 27 NPT	7/8"
PA21	1/8" - 27 NPT	1"
PA22	1/8" - 27 NPT	1-1/2"
PA23	1/8" - 27 NPT	2"
PA24	1/8" - 27 NPT	2-1/2"
PIPE CLAMP AND BAYONET ADAPTERS		
Part Number	Band Diameter	Adapter Length (L)
PA30	1-1/4" to 2-1/4"	1"
PA31	1-1/4" to 2-1/4"	2"
PA32	2-1/4" to 3-1/4"	1"
PA33	2-1/4" to 3-1/4"	2"
PA34	3-1/4" to 4-1/4"	1"
PA35	3-1/4" to 4-1/4"	2"
PA36	4-1/4" to 5"	1"
PA37	4-1/4" to 5"	2"