



**REPLACEMENT PARTS  
RE-ORDER FORM**



180 Dexter Avenue, P.O. Box 9143  
Watertown, MA 02471-9143 USA

T: 617 923-6966  
F: 617 926-8411  
W: www.appliedsensortech.com

Company Name: \_\_\_\_\_

Ship To: \_\_\_\_\_

City/ST/Zip: \_\_\_\_\_

Contact Name: \_\_\_\_\_

Phone: \_\_\_\_\_

P.O.#: \_\_\_\_\_

PARTS FOR .250" DIAMETER SENSORS		
Qty	Part Number	Description
<b>Thermocouple pods (48" leads)</b>		
	MI1113( )G	Grounded, fiberglass leads, specify J,K,E,T
	MI1113( )U	Ungrounded, fiberglass leads, specify J,K,E,T
	MI1113TF( )G	Grounded, Teflon leads, specify J,K,E,T
	MI1113TF( )U	Ungrounded, Teflon leads, specify J,K,E,T
<b>100-ohm RTD pods</b>		
	RT1254	3-wire, fiberglass leads
	RT1260	3-wire, Teflon leads
	RT1276	4-wire, fiberglass leads
	RT1257	4-wire, Teflon leads
<b>Housings (stainless steel, one closed end)</b>		
	HS2512	12" long
	HS2524	24" long
	HS2536	36" long
	HS2548	48" long
<b>Spring-loading kits</b>		
	AC1087	For spring-loading in NEMA 4 heads
	PF14	1/2" x 1/2" stst hex fitting
	PF22	1/2" x 1/2" stst hex fitting, w/o-ring
<b>Compression Fittings (316 stst body and nut)</b>		
	PF65	1/4" NPT, 316 stst ferrule
	PF66	1/4" NPT, Teflon ferrule
	PF73	1/2" NPT, 316 stst ferrule
	PF74	1/2" NPT, Teflon ferrule
<b>Misc.</b>		
	TS1092	Nylon strain relief grommet (bag of 10)
	B1250	Brass crimp insert for plug connection
	TS1093	3' stst armor and adaptor

PARTS FOR .188" DIAMETER SENSORS		
Qty	Part Number	Description
<b>Thermocouple pods</b>		
	MI1115( )G	Grounded, fiberglass leads, specify J,K,E,T
	MI1115( )U	Ungrounded, fiberglass leads, specify J,K,E,T
	MI1115TF( )G	Grounded, Teflon leads, specify J,K,E,T
	MI1115TF( )U	Ungrounded, Teflon leads, specify J,K,E,T
<b>100-ohm RTD pods</b>		
	RT1184	3-wire, fiberglass leads
	RT1256	3-wire, Teflon leads
<b>Housings (stainless steel, one closed end)</b>		
	HS1812	12" long
	HS1824	24" long
	HS1836	36" long
	HS1848	48" long
<b>Spring-loading kits</b>		
	AC1088	For spring-loading in NEMA 4 heads
	PF13	1/2" x 1/2" stst hex fitting
	PF21	1/2" x 1/2" stst hex fitting, w/o-ring
<b>Compression Fittings</b>		
	PF55	1/4" NPT, 316 stst ferrule
	PF56	1/4" NPT, Teflon ferrule
	PF59	1/2" NPT, 316 stst ferrule
	PF60	1/2" NPT, Teflon ferrule
<b>Misc.</b>		
	TS1094	Teflon strain relief insert (bag of 10)
	B1188	Brass crimp insert for plug connection

COMMON PARTS FOR BOTH .250" AND .188" DIAMETERS		
QTY	Part Number	Description
<b>Terminal Heads (include Term. Block)</b>		
	PH01	Aluminum, ord. location, 1/2" conduit
	PH02	Aluminum, ord. location, 3/4" conduit
	PH04	Cast iron, ord. location, 1/2" conduit
	PH05	Cast iron, ord. location, 3/4" conduit
	PH23	Black polypropylene, 3/4" conduit
	PH24	White polypropylene, 3/4" conduit
	PH47	316 stst, ord. location, 3/4" conduit
	PH50	Aluminum, explosion-proof, 1/2" conduit
	PH51	Aluminum, explosion-proof, 3/4" conduit
<b>Terminal Blocks</b>		
	PH41	4-post, ceramic
	PH48	3-post, ceramic, for PH50/PH51 heads

QTY	Part Number	Description
<b>Nipples and Unions (1/2" NPT)</b>		
	NC100( )	c.s. nipple (specify length - 1,2,3,4,6")
	NS100( )	stst nipple (specify length - 1,2,3,4,6")
	US1011	Union, stst, ordinary location
	HF1091	Union, plated steel, explosion-proof
<b>Plugs and Jacks</b>		
	PT05( )	T/C plug (specify J,K,E,T - e.g., PT05-J)
	PT05-3	3-pin RTD plug
	PT06( )	T/C jack (specify J,K,E,T - e.g., PT06-J)
	PT06-3	3-pin RTD jack
	PA10	Wire clamp